

UPM Office multifunction

Choose UPM Office cut-size papers when you need to be absolutely sure to produce optimal printing quality. Suitable for anything from superior-quality colour printouts to functional high speed copying.

Recommended end-uses

Colour diagrams | Direct mailing | Documents | Fax papers | Flyers | High-quality documents | Manuals | Memos | Newsletters | Office applications | Office paper | Product data sheets | Reports | Transactional / transpromotional documents

Product information

| Regions | Africa Europe Middle East South America |
|------------------|---|
| Business contact | UPM Communication Papers |
| Category | Office papers |
| Description | Great all-round office paper with excellent colour contrasts and colour reproduction. |
| Grade | Woodfree uncoated (WFU) |
| Finish | Machine finished |
| Furnish | Chemical pulp |
| Printing method | B/W inkjet printing B/W laser printing (dry toner) Colour inkjet printing Colour laser printing (dry toner) Copying Fax |
| Format/Size | A3 A4 A5 |
| Wrapping | UPM Asendo™ Strong kraft paper Strong moisture proof polyethylene laminated kraft paper |
| Note | PEFC™ certified. 70 g/m² available on request. |

Certificates

| Product Compliance | EU Ecolabel Permanent Paper ISO 9706 |
|--------------------|---|
| Fibre Certificates | PEFC Chain-of-Custody |
| Mill Certificates | EMAS ISO 14001 ISO 50001 ISO 9001 ISO 45001 |

Technical target values

| Basis weight (ISO 536) (g/m²) | 70.0 | 75.0 | 80.0 | 90.0 | 100.0 |
|--|-------|-------|-------|-------|-------|
| Thickness (ISO 534) (µm) | 102.0 | 105.0 | 106.0 | 117.0 | 130.0 |
| CIE Whiteness (ISO 11475:2017) | 164.0 | 164.0 | 164.0 | 164.0 | 164.0 |
| Brightness D65 (ISO 2470-2) (%) | 108.0 | 108.0 | 108.0 | 108.0 | 108.0 |
| Opacity ISO (2471) (%) | 92.0 | 93.5 | 94.5 | 95.5 | 96.5 |
| Roughness Bendtsen (ISO 8791-2) (ml/min) | 250.0 | 250.0 | 250.0 | 250.0 | 250.0 |

Please note: Technical values are informative and subject to production variations.